



# SNEAK TRIMLESS

CEILING RECESSED



## 1.0 LED

LED 7/10W | 350-500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.26 kg IP20  $\theta_{c} < 0,3^{\circ}$

86x86  $\phi < 35^{\circ}/35^{\circ}$   $\psi < 355^{\circ}$   $\eta > 95$   $\epsilon < 4-25$

CODE

155151W  
155151B

### Light Colour Selection

	LUMEN	CRI	CODE
2700K	420-590	>90	3
3000K	470-640	>90	5
1800-2850K	320-440	>90	9

## ALWAYS USE

power supply

CODE

350mA | 10W 90213402  
500mA | 10W 90214403  
500mA | 15W dim 90224501

## 2.0 LED

2xLED 7/10W | 350-500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.33 kg IP20  $\theta_{c} < 0,3^{\circ}$

86x156  $\phi < 35^{\circ}/35^{\circ}$   $\psi < 355^{\circ}$   $\eta > 95$   $\epsilon < 4-25$

CODE

155251W  
155251B

### Light Colour Selection

	LUMEN	CRI	CODE
2700K	2x420-590	>90	3
3000K	2x470-640	>90	5
1800-2850K	2x320-440	>90	9

## ALWAYS USE

power supply

CODE

350mA | 10W 90213402  
500mA | 10W 90214403  
500mA | 15W dim 90224501