



SNEAK TRIMLESS

CEILING RECESSED



1.0 LED

LED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.26 kg IP20 $\theta_{c} < 0,3^{\circ}$

86x86 $\phi < 35^{\circ}/35^{\circ}$ $\psi < 355^{\circ}$ $\eta > 95$ $\epsilon < 4-25$

CODE

155151W
155151B

Light Colour Selection

	LUMEN	CRI	CODE
2700K	420-590	>90	3
3000K	470-640	>90	5
1800-2850K	320-440	>90	9

ALWAYS USE

power supply

CODE

350mA 10W	90213402
500mA 10W	90214403
500mA 15W dim	90224501

2.0 LED

2xLED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.33 kg IP20 $\theta_{c} < 0,3^{\circ}$

86x156 $\phi < 35^{\circ}/35^{\circ}$ $\psi < 355^{\circ}$ $\eta > 95$ $\epsilon < 4-25$

CODE

155251W
155251B

Light Colour Selection

	LUMEN	CRI	CODE
2700K	2x420-590	>90	3
3000K	2x470-640	>90	5
1800-2850K	2x320-440	>90	9

ALWAYS USE

power supply

CODE

350mA 10W	90213402
500mA 10W	90214403
500mA 15W dim	90224501